


# OSCA ESTRAIBILI



COD	MASS FLOW Kg/h	Ø IN/OUT UNI EN 1092-1 PN6	A mm	B mm	C mm
06FCE00001	288	DN 80	400	220	270
06FCE00002	324	DN 80	420	240	280
06FCE00003	504	DN 100	440	270	300
06FCE00004	576	DN 100	470	320	350
06FCE00005	828	DN 125	510	370	400
06FCE00006	1188	DN 150	580	470	500
06FCE00007	2340	DN 200	610	510	550
06FCE00008	3132	DN 250	640	560	600
06FCE00009	3600	DN 250	680	610	650
06FCE00010	4680	DN 300	710	660	700
06FCE00011	5040	DN 300	750	710	750
06FCE00012	5760	DN 350	780	760	800
06FCE00013	6408	DN 350	810	810	850
06FCE00014	9000	DN 500	850	860	900
06FCE00015	10440	DN 500	920	960	1000
06FCE00016	13680	DN 600	1000	1060	1100

<b>Contropressione</b>	10 mbar con portate indicate @ 400°C
<b>Materiali</b>	Aisi 304 - flange FE
<b>Finitura:</b>	Verniciatura siliconica grigio silver RAL 9006
<b>Pres a pressione</b>	Manicotto Gas 3/8" ISO 228/1 lunghezza 120 mm

## Accessori opzionali / varianti

Flange in Aisi 304  
 Flange girevoli  
 Flange personalizzate  
 Controflange  
 Guarnizioni  
 Bulloneria