

RAY FS WP 456/457

HYDROMETER

FLOW SENSOR | MECHANICAL



APPLICATION

Volume measuring component for measuring heat for billing hot water consumption

FEATURES

- ▶ Facility for remote transmission of flow rates
- ▶ For installation in any position
- ▶ Encapsulated and evacuated counter
- ▶ Counter can be rotated as required for easier reading
- ▶ Easily replaceable reed switch
- ▶ Contact rating (without series resistor) max. 24 V (SELV) 0.2 A
- ▶ Very low pressure loss
- ▶ Sealed shield protects against magnetic interference
- ▶ The reed switch is fitted with a 100 Ω , 1/4 W protective resistor (cable length 3 m). Can be ordered without series resistor
- ▶ Outstanding long-term accuracy achieved by mounting vane in ring sapphire and carbide bearing
- ▶ Condensation-proof transparent cover for unobstructed reading
- ▶ Completely dry-running - no gears in the wet chamber
- ▶ Please note: Flow sensor for heat measurement

RAY FS WP 456/457

FLOW SENSOR | MECHANICAL

GENERAL

RAY FS WP 456/457			
Medium temperature range	°C	0 ... 120	
Medium temperature range with counter extension	°C	0 ... 130	
Nominal pressure	PN	bar	16*
Protection class	IP 65		

* See also special versions.

TECHNICAL DATA ACCORDING NATIONAL APPROVAL

Nominal diameter	DN	mm	50	65	80	100	125	150
Nominal flow rate	Q_n	m³/h	-	-	-	60	100	-
Permissible continuous load (HY)		m³/h	-	-	-	70	100	-
Maximum flow rate (short-term)	Q_{max}	m³/h	-	-	-	180	250	-
Transition flow rate	Q_t	m³/h	-	-	-	9	15	-
Minimum flow rate	Q_{min}	m³/h	-	-	-	2	3	-
Starting flow rate		l/h	-	-	-	400	600	-
Flow rate at 0.1 bar pressure loss		m³/h	-	-	-	95	200	-
Flow resistance coefficient Zeta			-	-	-	18	9.9	-
Pulse value reed switch		l/pulse	-	-	-	25 / 100 / 250 / 1000	25 / 100 / 250 / 1000	-

Nominal diameter	DN	mm	200	250	300	400	500
Nominal flow rate	Q_n	m³/h	-	400	600	1000	1500
Permissible continuous load (HY)		m³/h	-	400	600	1000	1500
Maximum flow rate (short-term)	Q_{max}	m³/h	-	800	1000	2000	3000
Transition flow rate	Q_t	m³/h	-	45	50	150	225
Minimum flow rate	Q_{min}	m³/h	-	25	30	40	60
Starting flow rate		l/h	-	2500	5000	-	-
Flow rate at 0.1 bar pressure loss		m³/h	-	1300	2000	3000	6000
Flow resistance coefficient Zeta			-	3.8	3.3	-	-
Pulse value reed switch		l/pulse	-	250 / 1000 / 2500 / 10000	250 / 1000 / 2500 / 10000	250 / 1000 / 2500 / 10000 / 25000 / 100000	250 / 1000 / 2500 / 10000 / 25000 / 100000

RAY FS WP 456/457

FLOW SENSOR | MECHANICAL

TECHNICAL DATA ACCORDING EN APPROVAL

Nominal diameter	DN	mm	50	65	80	100	125	150
Nominal flow rate	q_p	m³/h	15	25	32	-	-	200
Short-term maximum flow rate (1x24 h)		m³/h	60	60	90	-	-	300
Maximum flow rate (short-term)	q_s	m³/h	30	30	45	-	-	300
Minimum flow rate	q_i	m³/h	0.6	1	3.2	-	-	8
Lower measuring range limit (± 5 %)			0.55	0.55	2.5	-	-	4.5
Starting flow rate		l/h	130	130	400	-	-	1500
Pressure loss at q_p	Δp	bar	0.02	0.02	0.01	-	-	0.02
Flow rate at 0.1 bar pressure loss		m³/h	35	63	102	-	-	310
Flow resistance coefficient Zeta			0.5	1.4	0.7	-	-	8.6
Pulse value reed switch		l/pulse	25 / 100 / 250 / 1000	25 / 100 / 250 / 1000	25 / 100 / 250 / 1000	-	-	100 / 250 / 1000

Nominal diameter	DN	mm	200	250	300	400	500
Nominal flow rate	q_p	m³/h	250	-	-	-	-
Short-term maximum flow rate (1x24 h)		m³/h	500	-	-	-	-
Maximum flow rate (short-term)	q_s	m³/h	500	-	-	-	-
Minimum flow rate	q_i	m³/h	10	-	-	-	-
Lower measuring range limit (± 5 %)			8	-	-	-	-
Starting flow rate		l/h	2000	-	-	-	-
Pressure loss at q_p	Δp	bar	0.02	-	-	-	-
Flow rate at 0.1 bar pressure loss		m³/h	550	-	-	-	-
Flow resistance coefficient Zeta			7	-	-	-	-
Pulse value reed switch		l/pulse	100 / 250 / 1000	-	-	-	-

DISPLAY RANGE

Nominal diameter	DN	mm	50	65	80	100	125	150
0.5 l ... 999,999 m³			•	•	•	•	•	
5.0 l ... 9,999,999 m³								•
50 l ... 99,999,999 m³								

Nominal diameter	DN	mm	200	250	300	400	500
0.5 l ... 999,999 m³							
5.0 l ... 9,999,999 m³			•				
50 l ... 99,999,999 m³				•	•	•	•

APPROVAL



Nominal diameter	DN	mm	50	65	80	100	125	150
National			-	-	-	22.16 / 87.01	22.16 / 87.01	-
EN approval 1434			22.56 / 01.01	22.56 / 01.01	22.56 / 01.01	-	-	22.56 / 03.02
Metrological class			$q_p / q_i = 25$	$q_p / q_i = 25$	$q_p / q_i = 10$	A•H/V	A•H/V	$q_p / q_i = 25$

Nominal diameter	DN	mm	200	250	300	400	500
National			-	-	-	-	-
EN approval 1434			22.56 / 03.02	-	-	-	-
Metrological class			$q_p / q_i = 25$	-	-	-	-

RAY FS WP 456/457

FLOW SENSOR | MECHANICAL

DIMENSIONS



Nominal diameter	DN	mm	50	65	80	100	125	150
Overall length	L	mm	200	200	200 / 225	250	250	300
Flange diameter	D	mm	165	185	200	220	250	285
Hole circle diameter	K	mm	125	145	160	180	210	240
Number of screwholes		pcs	4	4	8	8	8	8
Screwhole diameter	D1	mm	18	18	18	18	18	22
Height	H	mm	75	82.5	94	110	125	135
Height (without counter extension)	H1	mm	141	141	141	200	200	244
Height (with counter extension)	H1	mm	182	182	182	240	240	284
Diameter	Ø B	mm	150	150	150	220	250	285
Weight		kg	11.1	11.6	12.5	19.8	22.4	39

Nominal diameter	DN	mm	200	250	300	400	500
Overall length	L	mm	350	450	500	500	500
Flange diameter	D	mm	240	405	460	580	715
Hole circle diameter	K	mm	295	350 / 355	400 / 410	515 / 525	620 / 650
Number of screwholes		pcs	8 / 12	12	12	16	20
Screwhole diameter	D1	mm	22	23 / 27	23 / 27	26 / 30	26 / 33
Height	H	mm	163	203	230	290	358
Height (without counter extension)	H1	mm	244	240	270	316	399
Height (with counter extension)	H1	mm	284	280	310	356	440
Diameter	Ø B	mm	240	405	460	-	-
Weight		kg	49	108	136	190	300

NOTE

When using the contact water meters as volume measuring component, we recommend that the meters are selected so that the pressure loss of 0.1 bar is not exceeded at maximum load.


SPECIAL VERSIONS

- Versions with different nominal pressure on request


RAY FS WP 456/457

FLOW SENSOR | MECHANICAL

PRESSURE LOSS GRAPH / TYPICAL ERROR GRAPH



Pressure loss graph



Typical error graph

HYDROMETER

HYDROMETER GmbH · Postfach 1462 · 91505 Ansbach
Tel. +49 981 1806-0 · Fax: +49 981 1806-615 · info@hydrometer.de · www.hydrometer.de
Subject to technical adjustments